Express Mail #ET029404528US

APPLICATION

FOR

UNITED STATES LETTERS PATENT

APPLICANT NAME: Charles Boice *et al.*

TITLE: METHOD FOR PERFORMING INTEGER DIVIDES WITHOUT PROPAGATION OF TRUNCATION ERROR

DOCKET NO.: END920010005US1

INTERNATIONAL BUSINESS MACHINES CORPORATION

METHOD FOR PERFORMING INTEGER DIVIDES WITHOUT PROPAGATION OF TRUNCATION ERROR

Background of the Invention

1. Technical Field

5   The present invention relates to a method and algorithm for performing a sequence of

integer divides without propagation of truncation error.

2. Related Art

Real-time video systems requiring large network bandwidth generally have their video

signals compressed so that the video signals may be efficiently transmitted from source to

10   destination. An example of an emerging video compression standard is the Moving Picture

Experts Group (MPEG) standard. Under MPEG, video frames are initially encoded (i.e.,

compressed) for efficient transmission, placed in a buffer, and subsequently decoded (i.e.,

uncompressed) for viewing.

During the encoding and decoding of video signals, a Video Buffering Verifier (VBV)

15   buffer is dynamically filled with binary bits of encoded video data at a variable rate (in

bits/frame), and the video data is subsequently removed from the buffer at a constant rate (in

bits/frame) for decoding purposes. The constant bits/frame removal rate is referred to herein as

an average bits/frame (BA), which is computed as

$$BA = BR/FR \tag{1}$$

wherein BR is a bit rate in bits/second and FR is a frame rate in frames/sec. If integer arithmetic

is used by buffer management software to compute BA, then Equation (1) should be recast into

an integer format. For example if FR=29.97 frames/sec, then

$$BA \quad = BR/29.97$$

$$= BR/(30-.03)$$

$$= BR/(30-30/1000)$$

$$= BR/(30(1-1/1000)) \tag{2}$$

Expanding (1-1/1000) in a Taylor series,

$$(1-1/1000)^{-1} = 1 + 1/1000 + \text{terms of second order and higher in } 1/1000 \tag{3}$$

Thus to first order, substitution of Equation (3) into Equation (2) yields:

$$BA = (BR + BR/1000)/30 \tag{4}$$

Equation (4) is a representation of Equation (1) to first order of 1/1000. Unfortunately, integer

division by 1000 and by 30 in Equation (4) causes truncation error, which results in a smaller

computed value of BA than is the "true" value of BA. The "true" value of BA is the constant

number of bits/frame physically removed, while the smaller computed value of BA is the

bits/frame that the buffer management software tracks as being removed based on Equation (4).

For example, if BR=29970 bits/sec, then using Equation (4) with floating point arithmetic yields

a "true" value of 1000 bits/frame (actually 999.999 bits/frame) for BA, but using Equation (4)

with integer divides by 1000 and 30 yields a smaller computed of 999 bits/frame for BA.

Accordingly with integer divides, the buffer management software would account for removal of

video data at 999 bits/frame from the VBV buffer, while in actuality 1000 bits/frame is

physically removed from the VBV buffer. If B represents the number of bits stored in the VBV buffer at any given time, then B will be computed as a smaller value B_C by the buffer management software than the true value B_T. As video frames are processed, $B_T - B_C$ will grow in magnitude and thus pose a risk that eventually B_C will be so small in comparison with B_T that the buffer management software will erroneously attempt to extract more bits from the VBV buffer than is actually in the VBV buffer. In accordance with the MPEG-2 standards, such an erroneous attempt would cause a VBV buffer violation labeled as "buffer overflow."

Thus, there is a need to avoid buffer overflow during encoding and decoding of video frames of a video signal.

Summary of the Invention

The present invention provides a method for computing an average bits/frame (BA) for frames extracted from a buffer used for video encoding and decoding, each said frame having a same number of fields, said BA equal to (BR + BR1/J1)/J2, said BR1, J1, and J2 each a positive integer, said BR a bit rate in bits/sec, said BR1/BR a positive integer, said method comprising:

determining BR1, J1, and J2 such that J2/(1+(BR1/BR)/J1) as evaluated in floating point is approximately equal to FR, said FR a frame rate in frames/sec;

calculating a quotient Q1 and remainder R1 from integer division of BR1 by J1;

calculating a quotient Q2 and remainder R2 from integer division of (BR+Q1) by J2;

initializing to zero accumulators A1 and A2; and

executing N iterations, wherein N > 1, and wherein executing each iteration includes:

adding R1 to A1;

if $A1 \geq J1$, then adding 1 to A2 and decrementing A1 by J1;

setting BA=Q2 and adding R2 to A2;

if $A2 \geq J2$, then adding 1 to BA and decrementing A2 by J2.

The present invention provides a computer code that computes an average bits/frame

(BA) for frames extracted from a buffer used for video encoding and decoding, each said frame

having a same number of fields, said BA equal to (BR + BR1/J1)/J2, said BR1, J1, and J2 each a

positive integer, said BR a bit rate in bits/sec, said BR1/BR a positive integer, said computer

code including an algorithm programmed to:

determine BR1, J1, and J2 such that J2/(1+(BR1/BR)/J1) as evaluated in floating point is

approximately equal to FR, said FR a frame rate in frames/sec;

calculate a quotient Q1 and remainder R1 from integer division of BR1 by J1;

calculate a quotient Q2 and remainder R2 from integer division of (BR+Q1) by J2;

initialize to zero accumulators A1 and A2; and

execute N iterations, wherein N > 1, and wherein to execute each iteration includes:

to add R1 to A1;

if $A1 \geq J1$, then to add 1 to A2 and to decrement A1 by J1;

to set BA=Q2 and to add R2 to A2; and

if $A2 \geq J2$, then to add 1 to BA and to decrement A2 by J2.

The present invention provides a method of computing an average bits/frame (BA) for

frames extracted from a buffer used for video encoding and decoding, each said frame having a

variable number of fields, comprising:

defining BA1 as an average bits/frame for a two-field frame, said BA1 equal to (BR + BR1/J1)/J2, said BR1, J1, and J2 each a positive integer, said BR a bit rate in bits/sec, said BR1/BR a positive integer;

defining BA2 as an average bits/frame for a one-field frame, said BA2 equal to (BR + BR1/J1)/(2*J2);

determining BR1, J1, and J2 such that J2/(1+(BR1/BR)/J1) as evaluated in floating point is approximately equal to FR, said FR a frame rate in frames/sec;

calculating a quotient Q1 and remainder R1 from integer division BR1/J1;

calculating a quotient Q2 and remainder R2 from integer division (BR+Q1)/J2;

calculating a quotient Q3 and remainder R3 from integer division (BR+Q1)/(2*J2);

initializing to zero accumulators A1, A2, B1, and B2;

executing N iterations, wherein N > 1, said executing iteration n of N relating to extracting a frame n from the buffer, said executing of iteration n including:

calculating BA1, including:

adding R1 to A1;

if $A1 \geq J1$ then adding 1 to A2 and decrementing A1 by J1;

setting BA1=Q2 and adding R2 to A2;

if $A2 \geq J2$, then adding 1 to BA1 and decrementing A2 by J2;

determining a number of fields F_n comprised by the frame n;

if F_n is even then setting BA2=0 else calculating BA2 including:

adding R1 to B1;

if $B1 \geq J1$, then adding 1 to B2 and decrementing B1 by J1;

setting BA2=Q3 and adding R3 to B2;

if $B2 \geq (2*J2)$, then adding 1 to BA2 and decrementing B2 by $(2*J2)$;

computing $BA=(F_n/2)*BA1 + BA2$, said $(F_n/2)$ computed by integer division.

The present invention provides a computer code that computes an average bits/frame

(BA) for frames extracted from a buffer used for video encoding and decoding, each said frame

having a variable number of fields, said BA a function of BA1 and BA2, said BA1 defined as an

average bits/frame for a two-field frame, said BA1 equal to $(BR + BR1/J1)/J2$, said BR1, J1, and

J2 each a positive integer, said BR a bit rate in bits/sec, said BR1/BR a positive integer, said

BA2 defined as an average bits/frame for a one-field frame, said BA2 equal to $(BR +$

$BR1/J1)/(2*J2)$, said computer code including an algorithm, said algorithm programmed to:

determine BR1, J1, and J2 such that $J2/(1+(BR1/BR)/J1)$ as evaluated in floating point is

approximately equal to FR, said FR a frame rate in frames/sec;

calculate a quotient Q1 and remainder R1 from integer division BR1/J1;

calculate a quotient Q2 and remainder R2 from integer division $(BR+Q1)/J2$;

calculate a quotient Q3 and remainder R3 from integer division $(BR+Q1)/(2*J2)$;

initialize to zero accumulators A1, A2, B1, and B2;

execute N iterations, wherein $N > 1$, said iteration n of N relating to extracting a frame n

from the buffer, wherein to execute iteration n includes:

to calculate BA1, including:

to add R1 to A1;

if $A1 \geq J1$ then to add 1 to A2 and to decrement A1 by J1;

to set BA1=Q2 and to add R2 to A2;

if $A2 \geq J2$, then to add 1 to BA1 and to decrement A2 by J2;

to determine a number of fields F_n comprised by the frame n;

if F_n is even then to set BA2=0 else to calculate BA2 including:

to add R1 to B1;

if $B1 \geq J1$, then to add 1 to B2 and to decrement B1 by J1;

to set BA2=Q3 and to add R3 to B2;

to compute $BA = (F_n/2)*BA1 + BA2$, said $(F_n/2)$ computed by integer division.

The present invention provides a method for computing Z, said $Z = \sum_n Z_n$, said $\sum_n$

denoting a summation over n from 1 to N, said N a positive integer of at least 1, said $Z_n = X_n/Y$,

said $X_n = (I_{1n}/J_1)M_{1n} + (I_{2n}/J_2)M_{2n} + ... +$

$(I_{Kn}/J_K)M_{Kn}$, said Y and said I_{kn}, J_k, M_{kn} (k=1, 2, ..., K) each a positive integer, said K a positive

integer of at least 1, said method comprising:

setting Z=0, B=0, and A_k=0 for k=1, 2, ..., K;

executing N iterations, said executing of iteration n of N including:

calculating a quotient Q_{kn} and a remainder R_{kn} from integer division I_{kn}/J_k for k=1,

2, ..., K;

calculating $X_n = \sum_k [Q_{kn}M_{kn}]$ as summed over k from 1 to K;

adding $R_{kn}M_{kn}$ to A_k for k=1, 2, ..., K;

for k = 1, 2, ..., K, if $A_k \geq J_k$, then adding 1 to B and decrementing A_k by J_k;

if $Y \neq 1$ then calculating a quotient Q_n and a remainder R_n from integer division X_n/Y, else setting $Q_n = X_n$ and $R_n = 0$;

setting $Z_n = Q_n$ and adding R_n to B;

if $B \geq Y$, then calculating $Z_n = Z_n + 1$ and decrementing B by Y;

adding Z_n to Z.

The present invention provides a computer code that computes Z, said $Z = \Sigma_n \ Z_n$, said Σ_n denoting a summation over n from 1 to N, said N a positive integer of at least 1, said $Z_n = X_n/Y$, said $X_n = (I_{1n}/J_1)M_{1n} + (I_{2n}/J_2)M_{2n} + ... + (I_{Kn}/J_K)M_{Kn}$, said Y and said I_{kn}, J_k, M_{kn} (k=1, 2, ..., K) each a positive integer, said K a positive integer of at least 1, said computer code including an algorithm, said algorithm programmed to:

set Z=0, B=0, and A_k=0 for k=1, 2, ..., K;

execute N iterations, wherein to execute iteration n of N includes:

to calculate a quotient Q_{kn} and a remainder R_{kn} from integer division I_{kn}/J_k for k=1, 2, ..., K;

to calculate $X_n = \Sigma_k \ [Q_{kn}M_{kn}]$ as summed over k from 1 to K;

to add $R_{kn}M_{kn}$ to A_k for k=1, 2, ..., K;

for k = 1, 2, ..., K, if $A_k \geq J_k$, then to add 1 to B and to decrement A_k by J_k;

if $Y \neq 1$ then to calculate a quotient Q_n and a remainder R_n from integer division X_n/Y, else to set $Q_n = X_n$ and $R_n = 0$;

to set $Z_n = Q_n$ and to add R_n to B;

if B $\geq$ Y, then to calculate $Z_n = Z_n + 1$ and to decrement B by Y;

to add Z_n to Z.

The present invention avoids buffer overflow during encoding and decoding of video

frames of a video signal.

Brief Description of the Drawings

5

FIG. 1 is a flow chart showing an iterative calculation of extracted bits/frame

(BA_FINAL) of video processing in terms of a single-picture bits/frame (BA_FINAL1) and half-

picture bits/frame single-picture bits/frame (BA_FINAL2), in accordance with embodiments of

the present invention.

10

FIG. 2 is a flow chart for calculation of the single-picture bits/frame (BA_FINAL1) of

FIG. 1, in accordance with embodiments of the present invention.

FIG. 3 is a flow chart for calculation of the half-picture bits/frame (BA_FINAL2) of

FIG. 1, in accordance with embodiments of the present invention.

FIG. 4 is a table illustrating iterations of FIG. 1 for the BA_FINAL1 calculation of FIG. 2

15

for an example, in accordance with embodiments of the present invention.

FIG. 5 is a table illustrating iterations of FIG. 1 for the BA_FINAL2 calculation of FIG. 3

for an example, in accordance with embodiments of the present invention.

FIG. 6 is a flow chart for an iterative calculation with integer division, in accordance with

embodiments of the present invention.

20

FIG. 7 is a flow chart for an iterative summation calculation with integer division, in

accordance with embodiments of the present invention.

FIG. 8 is a table illustrating iterations of FIG. 7 for an example, in accordance with embodiments of the present invention.

FIG. 9 illustrates a computer system, in accordance with embodiments of the present

5   invention.

Detailed Description of the Invention

Video compression under MPEG-2 includes three types of compression: spatial compression, temporal compression, and 3/2 compression. Spatial compression compresses data within a picture such as by use of discrete cosine transformation (DCT) coefficients to account

10   for spatial redundancy within the picture. Temporal compression compresses data between successive pictures such as through motion compensation (e.g., describing a picture in terms of vectors that relate portions of the picture to corresponding portions of the previous picture). 3/2 compression compresses 1½ pictures into 1 picture as will be explained as follows.

Under MPEG-2, there is a distinction between pictures, fields, and frames. A picture

15   comprises a physical screen of binary bits. Under MPEG-2, a picture consists of two interlacing fields, namely an upper field that includes bits on an upper portion of the picture and a lower field that includes bits on a lower portion of the picture. Each such field may be thought of as a half-picture. A frame is collection of fields that is stored in a Video Buffering Verifier (VBV) buffer as a unit. Under MPEG-2, a frame has either 2 fields or 3 fields and is called a 2-field

20   frame or a 3-field frame, respectively. An example of a 2-field frame is the upper and lower

END920010005US1   10

fields of a single picture. An example of a 3-field frame is the upper and lower fields of a first

picture followed by the upper field of a second (i.e., next) picture. With a 3-field frame having

fields sequentially denoted as fields 1, 2, and 3, the field 3 may be indistinguishable to a human

eye from the field 1. Thus with the previous example of a 3-field frame, the upper field of the

5   second picture is indistinguishable to the human eye from the upper field of the first picture.

Accordingly, field 3 of the 3-field frame is represented by a "repeat flag" that denotes repetition

of the bits of field 1. Since the 3-field frame includes only 2 fields of bits and the repeat flag, the

3-field frame represents a compression known as the "3/2 compression."

During video processing of the VBV buffer for subsequent decoding, BA bits/frame are

10   removed from the VBV buffer. Each such removal of BA bits from the VBV buffer constitutes

an "iteration" in a sequence of such removals. Upon such removal in an iteration, the buffer

management software must compute BA corresponding to the average number of bits/frame

removed and keep track of the number of bits present in the VBV buffer at the end of each

iteration. Equation (4) may be viewed as a calculation for BA corresponding to a 2-field frame

15   of a single picture. Thus if a 2-field frame is processed during an iteration, then Equation (4)

may be used for calculating BA. But if a 3-field frame is processed during an iteration, then BA

corresponding to 3 fields, or 1½ pictures, must be calculated. Thus a 3-field frame value of BA

is equal to BA of a single picture + half-BA of a single picture, which represents BA for 1½

pictures. Accordingly, calculation of BA for a given iteration depends on whether the frame of

20   extracted bits for the iteration is a 2-field frame or a 3-field frame, as depicted in FIGS. 1-3, in

accordance with embodiments of the present invention. FIGS. 1-3 are based on Equation (4)

END920010005US1   11

with modifications in accordance with the present invention.

FIG. 1 is a flow chart illustrating looping through iterations. In each iteration, the total

bits/frame (BA_FINAL) is calculated to represent the average number of bits/frame that is

extracted from the buffer in each iteration. As seen in block **20**, BA_FINAL is a sum of terms

BA_FINAL1 and BA_FINAL2. The term BA_FINAL1 represents BA for a 2-fields (i.e., full

picture) and is calculated as shown in FIG. 2. The term BA_FINAL2 represents BA for a 1-field

frame (i.e., half-picture) and is calculated as shown in FIG. 3. For a 2-field frame,

BA_FINAL2=0 and BA_FINAL = BA_FINAL1. For a 3-field frame, BA_FINAL is a sum of

BA for one picture (i.e., BA_FINAL1) and BA for a half-picture (i.e., BA_FINAL2), which in

composite represents 1½ pictures.

Block **10** of FIG. 1 includes initializations for the BA_FINAL1 calculations of FIG. 2 and

initializations for the BA_FINAL2 calculations of FIG. 3. The initialization block **10** will be

described *infra* in conjunction with FIGS. 2 and 3. Blocks **12, 14/16** or **14/18, and 20** are

executed within a single iteration. Thus, the blocks **12, 14/16** or **14/18**, and **20**, together with a

return path **22**, defines an iteration loop. Block **12** calculates BA_FINAL1 as described in FIG.

2. Decision block **14** asks whether the frame being processed for extraction is a 3-field frame. If

NO, then BA_FINAL2 is set equal to 0 (for a 2-field frame) as shown in block **16**. If YES, then

block **18** is executed, and block **18** calculates BA_FINAL2 (for a 3-field frame) as described in

FIG. 3. Block **20** sums BA_FINAL1 and BA_FINAL2 to calculate BA_FINAL for either a 2-

field frame or a 3-field frame. The path **22** effectuates a transition between successive iterations.

The flow chart of FIG. 1 may be modified in any manner that is logically equivalent to

FIG. 1 as shown herein, as would be understood by one of ordinary skill in the art. For example, blocks **16** and **18** could be replaced by the following logic. If NO is the answer to the query in decision block **14**, then BA_FINAL =BA_FINAL1 is executed. If YES is the answer to the query in decision block **14**, then BA_FINAL2 is calculated followed by execution of BA_FINAL

5 = BA_FINAL1 + BA_FINAL2.

FIG. 2 is a flow chart for calculation of BA_FINAL1 of the block **12** of FIG. 1. Thus the flow chart of FIG. 2 is within the iterations loop shown in FIG. 1. In FIG. 2, BA_FINAL1 is calculated, as shown in FIG. 2, as a function of BA1:

$$BA1 = (BR+BR/1000)/FR\_A \tag{5}$$

10 wherein BR is bit rate in bits/second expressed as a positive integer, wherein FR_A is a frame rate in frames/sec (e.g., frames/sec), and wherein the divisions by 1000 and FR_A are integer divisions with truncation of fractional remainders. It is assumed herein that "integer division" generally results in truncation of fractional remainders.

The initialization **10** of FIG. 1 comprises the following initializations for the

15 BA_FINAL1 calculation of FIG. 2:

$$adj\_t = BR/1000 \tag{6}$$

$$adt\_rem = BR - (1000*adj\_t) \tag{7}$$

$$ba\_t = (BR+adj\_t)/FR\_A \tag{8}$$

$$ba\_rem = (BR+adj\_t) - (FR\_A*ba\_t) \tag{9}$$

20 $$adj\_rem\_accum = 0 \tag{10}$$

$$ba\_rem\_accum = 0 \tag{11}$$

wherein the divisions by 1000 and FR_A in Equations (6) and (8), respectively, are by integer

division with truncation. For example, if BR=26320, BA1 would equal 878.21 in a floating

point implementation of Equation (5). With integer division, however, the initializations of

Equations (6)-(9) yield:

5   adj_t=26

         adj_rem=320

         ba_t=878

         ba_rem=6

Note that ba_t in Equation (8) is the truncated value of BA1 of Equation (5), as illustrated in the

10   preceding example such that the ba_t=878 and BA1 (floating point)= 878.21. As shown in the

block **66** of FIG. 2, BA_FINAL1 is equal to ba_t unless a parameter e_adder is equal to 1. The

parameter e_adder offsets the aforementioned truncation as will now be demonstrated.

      The remainders adj_rem and ba_rem are lost through truncation resulting from integer

division in Equations (6) and (8), respectively. To compensate for this truncation, the algorithm

15   of FIG. 2 saves and accumulates remainders adj_rem and ba_rem in accumulators

adj_rem_accum and ba_rem_accum, respectively, in each iteration of FIG. 1, as shown in blocks

32 and **48**, respectively, of FIG. 2. An "accumulator" is defined herein as a storage location for

storing a cumulative quantity (i.e., a summation). If in an iteration of FIG. 1, ba_rem_accum

accumulates to FR_A (e.g. 30) or greater, then the accumulator ba_rem_accum is decremented

20   by FR_A and BA_FINAL1 is incremented by 1 (i.e., e_adder=1 in FIG. 2), as shown in blocks

52, **58**, and **62**. If ba_rem_accum is less than FR_A, then e_adder is set to zero (see blocks **52**

and **56**) and BA_FINAL1 is not incremented by 1. Similarly, if in an iteration of FIG. 1,

adj_rem_accum in FIG. 2 accumulates to 1000 or greater, then the accumulator adj_rem_accum

is decremented by 1000 and the accumulator ba_rem_accum is incremented by 1 (i.e.,

ba_rem_adder=1 in FIG. 2), as shown in blocks **34, 42,** and **46**. If adj_rem_accum is less than

1000 in an iteration, then ba_rem_adder is set to zero (see blocks **34** and **38**) and ba_rem_accum

is not incremented by 1. It should be noted from block **48** that ba_rem_adder is an increment to

the accumulator ba_rem_accum. Thus the accumulators adj_rem_accum and ba_rem_accum

compensate for the truncation losses in computing BA1 of Equation (5) by integer division of

1000 and FR_A, respectively.

The flow chart of FIG. 2 may be modified in any manner that is logically equivalent to

FIG. 2 as shown herein, as would be understood by one of ordinary skill in the art. For example,

some or all of the intitializations of Equations (6)-(9), or mathematical equivalents thereof, could

alternatively be performed within the iteration loop of FIG. 2. Since adj_rem_accum and

ba_rem_accum are variables rather than constants, Equations (10) and (11) (or mathematical

equivalents thereof) could each alternatively be performed within the iteration loop of FIG. 2 but

only at the beginning of the first iteration.

FIG. 4 illustrates for the previous example (i.e., BR=26320) values at the end of each of

the first 11 iterations of: adj_rem_accum, ba_rem_adder, ba_rem_accum, e_adder, and

BA_FINAL1. In FIG. 4, BA_FINAL1 has the truncated value of 878 at the end of iterations 1-4,

6-9, and 11, but has a value of 879 in iterations 5 and 10. Hence, the algorithm of FIG. 2

mathematically extracts an extra bit in iterations 5 and 10 to compensate for the truncations in

iterations 1-4 and 6-9. Thus, the algorithm of FIG. 2 prevents propagation of the truncation error

by periodically simulating the effect of near-perfect integer division.

FIG. 3 is a flow chart for calculation of BA_FINAL2 of the block **18** of FIG. 1. Thus the

flow chart of FIG. 3 is within the iterations loop shown in FIG. 1. In FIG. 3, BA_FINAL2 is

5   calculated, as shown in FIG. 3, as a function of BA2:

$$BA2 = (BR+BR/1000)/(2*FR\_A) \tag{12}$$

wherein the divisions by 1000 and $2*FR\_A$ are integer divisions with truncation of fractional

remainders.

The initialization **10** of FIG. 1 comprises, in addition to initializations of Equations (6)-

10   (11), the following initializations for the BA_FINAL2 calculation of FIG. 3:

$$h\_adj\_t = BR/1000 \tag{13}$$

$$h\_adj\_rem = BR - (1000*h\_adj\_t) \tag{14}$$

$$h\_ba\_t = (BR+h\_adj\_t)/(2*FR\_A) \tag{15}$$

$$h\_ba\_rem = (BR+h\_adj\_t) - (2*FR\_A * h\_ba\_t) \tag{16}$$

15     $$h\_adj\_rem\_accum = 0 \tag{17}$$

$$h\_ba\_rem\_accum = 0 \tag{18}$$

wherein the divisions by 1000 and $2*FR\_A$ in Equations (13) and (15), respectively, are by

integer division with truncation. Note that h_adj_t and h_adj_rem of FIG. 3 are equal to adj_t

and adj_rem of FIG. 2. For the preceding example with BR=26320, BA2 would equal 439.105

20   in a floating point implementation of Equation (12). With integer division, however, the

initializations of Equations (13)-(14) yield:

END920010005US1   16

h_adj_t=26

h_adj_rem=320

h_ba_t=439

h_ba_rem=6

5   Note that h_ba_t in Equation (15) is the truncated value of BA2 of Equation (12), as illustrated in

the preceding example such that the h_ba_t=439 and BA2 (floating point)= 439.105.

Accordingly, BA_FINAL2 is equal to h_ba_t unless a parameter h_adder is equal to 1, as shown

in the block **166** of FIG. 3. The parameter h_adder offsets the aforementioned truncation as will

now be demonstrated.

10   The remainders h_adj_rem and h_ba_rem are lost through truncation resulting from

integer division in Equations (13) and (15), respectively. To compensate for this truncation, the

algorithm of FIG. 3 saves and accumulates remainders h_adj_rem and h_ba_rem in accumulators

h_adj_rem_accum and h_ba_rem_accum, respectively, in each "YES" iteration of FIG. 1 (i.e., an

iteration in which the answer to the question in the decision block **14** of FIG. 1 is "YES"), as

15   shown in blocks **132** and **148**, respectively, of FIG. 3. If in such a "YES" iteration of FIG. 1,

h_ba_rem_accum accumulates to 2*FR_A (i.e. 60) or greater, then the accumulator

h_ba_rem_accum is decremented by 2*FR_A and BA_FINAL2 is incremented by 1 (i.e.,

h_adder=1 in FIG. 3), as shown in blocks **152**, **158**, and **162**. If h_ba_rem_accum is less than

2*FR_A, then h_adder is set to zero (see blocks **152** and **156**) and BA_FINAL2 is not

20   incremented by 1. Similarly, if in such a "YES" iteration of FIG. 1, h_adj_rem_accum in FIG. 3

accumulates to 1000 or greater, then the accumulator h_adj_rem_accum is decremented by 1000

and the accumulator h_ba_rem_accum is incremented by 1 (i.e., h_ba_rem_adder=1 in FIG. 3), as shown in blocks **134, 142,** and **146.** If h_adj_rem_accum is less than 1000 in an iteration, then h_ba_rem_adder is set to zero (see blocks **134** and **138**) and h_ba_rem_accum is not incremented by 1. It should be noted from block **148** that h_ba_rem_adder is an increment to the accumulator

5   h_ba_rem_accum. Thus the accumulators h_adj_rem_accum and h_ba_rem_accum compensate for the truncation losses in computing BA2 of Equation (12) by integer division of 1000 and 2*FR_A, respectively.

The flow chart of FIG. 3 may be modified in any manner that is logically equivalent to FIG. 3 as shown herein, as would be understood by one of ordinary skill in the art. For example,

10   some or all of the intitializations of Equations (13)-(16), or mathematical equivalents thereof, could alternatively be performed within the iteration loop of FIG. 3. Since h_adj_rem_accum and h_ba_rem_accum are variables rather than constants, Equations (17) and (18) (or mathematical equivalents thereof) could each alternatively be performed within the iteration loop of FIG. 3 but only at the beginning of the first iteration.

15   FIG. 5 illustrates for the previous example (i.e., BR=26320) values at the end of each of "YES" iterations (i.e., iterations 3, 4, 6, 9-11, 15, 18-19, and 22-23) of: h_adj_rem_accum, h_ba_rem_adder, h_ba_rem_accum, h_adder, and BA_FINAL2. In FIG. 5, BA_FINAL2 has the truncated value of 439 at the end of iterations 3, 4, 6, 9-11, 15, 18-19, and 23, but has a value of 440 in iteration 22. Hence, the algorithm of FIG. 3 mathematically extracts an extra bit in

20   iteration 22 to compensate for the truncations in iterations 3, 4, 6, 9-11, 15, and 18-19. Thus, the algorithm of FIG. 3 prevents propagation of the truncation error by periodically simulating the

effect of near-perfect integer division.

While FIG. 1 implements 3/2 compression based on video encoding of either 2 fields/frame or 3 fields/frame, the scope of the present invention includes a more general F/2 compression, wherein F is the number of fields per frame such that F $\geq$3. With F/2 compression,

5   the question in decision box **14** of FIG. 1 is replaced by the following question: "Does this frame have F fields, wherein F $\geq$3?" Block **18** calculates BA_FINAL2 only if F is odd. Block **20** is changed to:

> BA_FINAL = (F/2) BA_FINAL1 + BA_FINAL2 (if F is odd) OR

> BA_FINAL = (F/2) BA_FINAL1 (if F is even)

10   wherein (F/2) is performed by integer division with truncation. For example, if F=3, which defines 3/2 compression, F/2=1 in integer division so that BA_FINAL = BA_FINAL1 + BA_FINAL2 as shown in block **20** of FIG. 1. As another example, if F=4, which defines 4/2 compression, F/2=2 in integer division so that BA_FINAL = 2*BA_FINAL1. While MPEG-2 currently limits F to 3, the present invention envisions inevitable advances in technology having

15   improved compression such that F > 3.

Equation (4) can be cast into a first different form by considering an example of FR=29.98 frames/sec in Equation (1). Using the same methodology that derived Equation (4), the following equation is derived:

> BA = (BR + (2*BR)/3000)/30   (19)

20   Equation (4) can be cast into a second different form by considering an example of FR=29.94 frames/sec in Equation (1). Using the same methodology that derived Equation (4),

the following equation is derived:

$$BA = (BR + BR/500)/30 \qquad (20)$$

Equation (4) can be cast into a third different form by considering an example of

FR=19.97 frames/sec in Equation (1). Using the same methodology that derived Equation (4),

the following equation is derived:

$$BA = (BR + (3*BR)/2000)/20 \qquad (21)$$

Equations (4), (12), and (19)-(20) may be considered special cases of the following more

general form:

$$BA = (BR + BR1/J1)/J2 \qquad (22)$$

wherein positive integers BR1, J1, and J2 are determined such that $J2/(1+(BR1/BR)/J1)$ as

evaluated in floating point is approximately equal to FR, and wherein BR1/BR is a positive

integer. BR1, J1, and J2 may be so determined by, *inter alia*: being calculated, being received as

input, or by being hard-coded within an algorithm that implements Equation (22). Equations (4),

(12), and (19)-(21) have the following common features: BR1/BR is a positive integer, J1 is a

multiple of 10, and J1 > J2. BA as computed from Equation (22) is "approximately equal" to

BR/FR (see Equation (1) for FR), which means that BA as computed from Equation (22) equals

BR/FR to an extent that terms of second or higher order in α (i.e., the terms α^2, α^3,...) are

negligible in comparison with linear terms in α in the Taylor series for $(1-\alpha)^{-1}$ wherein $\alpha =$

(BR1/BR)/J1, as illustrated for $\alpha=1/1000$ in the derivation of Equation (4) from Equation (1).

Note that $\alpha=2/3000$, 1/500, and 3/2000 in Equations (19), (20), and (21), respectively. Similarly,

$J2/(1+(BR1/BR)/J1)$ is "approximately equal" to FR. For a given FR and BR, there may be more

END920010005US1   20

than one combination of BR1, J1, and J2 such that $J2/(1+(BR1/BR)/J1)$ is "approximately equal" to FR.

Equation (22) is implemented as shown in the flow chart of FIG. 6, in accordance with embodiments of the present invention. The following initializations occur in block **70** of FIG. 6:

a quotient Q1 and a remainder R1 are calculated from integer division of BR1 by J1;

a quotient Q2 and a remainder R2 are calculated from integer division of (BR+Q1) by J2;

and a first accumulator A1 and a second accumulator A2 are each initialized to zero.

Following the aforementioned initializations, N iterations are executed, wherein $N > 1$. Each iteration includes blocks **72, 74, 76, 78, 80, 82,** and **84,** and return path **86.** Block **84** executes a test that determines whether any more iterations remain to be executed. Executing each iteration includes:

adding R1 to A1 (block **72**);

if $A1 \ge J1$ then adding 1 to A2 and decrementing A1 by J1 (blocks **74** and **76**);

calculating BA as equal to Q2 (block **78**);

adding R2 to A2 (block **78**); and

if $A2 \ge J2$ then adding 1 to BA and and decrementing A2 by J2 (blocks **80** and **82**).

Since Equation (22) encompasses Equations (5) and (12) as special cases, Equation (22) and the flow chart and algorithm of FIG. 6 could be used to implement the calculations of BA_FINAL1 and BA_FINAL2 of FIG. 2 and FIG. 3, respectively. Equivalently, Equation (22) and the flow chart and algorithm of FIG. 6 could be used to implement calculations of bits/frame (BA1) for two fields per frame (e.g., Equation (5)) and calculations of bits/frame (BA2) for one

END920010005US1   21

field per frame (e.g., Equation (6)). For calculating BA1=BA in Equation (22), the positive

integers BR1, J1, and J2 are determined such that $J2/(1+(BR1/BR)/J1)$ as evaluated in floating

point is approximately equal to FR. For calculating BA2=BA in Equation (22) in a manner that

is consistent with calculating BA1, J1 is replaced by 2*J1.

5   The flow chart of FIG. 6 may be modified in any manner that is logically equivalent to

FIG. 6 as shown herein, as would be understood by one of ordinary skill in the art. For example,

some or all of the intitializations block **70**, or mathematical equivalents thereof, could

alternatively be performed within the iteration loop of FIG. 6. Since accumulators A1 and A2

are variables rather than constants, initializations of A1=0 and A2 =0 (or mathematical

10   equivalents thereof) could each alternatively be performed within the iteration loop of FIG. 6 but

only at the beginning of the first iteration.

Equations (5) and (12), as well as Equation (22), which are computed with integer

division by the algorithms described by FIGS. 1-3 and 6, may be expressed in a more general

form as follows, in accordance with the present invention:

15        $Z_n = X_n/Y$ (23)

$X_n = (I_{1n}/J_1)M_{1n} + (I_{2n}/J_2)M_{2n} + ... + (I_{Kn}/J_K)M_{Kn}$ (24)

where "n" is an iteration index defining iterations analogous to the iterations described *supra* for

FIG. 1 and FIG. 6. I_{kn}, J_k, and M_{kn} (k=1, 2, ..., K; K $\geq$ 1) are positive integers, and I_{kn}/J_k is

performed by integer division with truncation. X_n and Y are positive integers and X_n/Y is

20   performed by integer division with truncation. Additionally, Y and J_k (k=1, 2, ..., K) cannot be

zero. As indicated in Equations (23)-(24), I_{kn} and M_{kn} (k=1, 2, ..., K) are permitted to vary with

iteration index n. Y and J_k (k=1, 2, ..., K) are assumed to be constant and thus do not vary with iteration index n. Z_n varies with iteration index n even if I_{kn} and I_{kn} do not vary with iteration index n, because the use of accumulators in accordance with the present invention causes Z_n to increase at selected iterations in order to prevent propagation of error.

5   The present invention could also be used to calculate the following summation:

$$Z = \Sigma_n \ Z_n \qquad\qquad\qquad\qquad (25)$$

wherein the summation over n in Equation (25) is from 1 to N, and wherein N is the total number of iterations.

Equations (23)-(24) reduce to Equation (5) if Y = FR_A, K = 2, I_{1n}=BR, J_1=1, M_{1n}=1,

10   I_{2n}=BR, J_2=1000, and M_{2n}=1. Note that 3/2 compression, or more generally F/2 compression described *supra*, could be modeled in Equations (23)-(24) by having M_{kn}=0 for those iterations in which the frame being processed has 2 fields, and M_{kn}=1 for those iterations in which the frame being processed has 3 fields, and suitable choices for Y, I_k, J_k, and M_k. For example, 3/2 compression, in combination with 2/2 compression, could be placed in the form of

15   BA_n = [BR + BR/1000 + (BR/2)*J_n + (BR/2000)*J_n]/FR_A

or BA_n = [2*BR + BR/500 + BR*J_n + (BR/1000)*J_n]/(2*FR_A)

such that J_n = 0 for iterations n having 2 fields/frame, and J_n = 1 for iterations n having 3 fields/frame. Note that the preceding equations for BA_n conform to the form of Equations (23)-(24).

20   Relative to FIGS. 1-3 and 6, and accompanying equations and text pertaining thereto as described *supra*, BR and FR may each be predetermined or received as input.

END920010005US1   23

The present invention computes Z_n in Equations (23)-(24) as described by FIG. 7. An

accumulator B accumulates remainders resulting from integer division by Y in Equation (23).

Accumulators A_1, A_2, ..., A_K accumulate remainders resulting from integer division by J_1, J_2, ...,

J_K, respectively, in Equation (24). Block **200** in FIG. 7 initializes to zero the accumulators B and

5   A_k (k=1, 2, ..., K) as well as the summation Z defined in Equation (25), as shown in Equations

(23)-(24). Looping begins at block **210**, and each loop iteration n includes blocks **210, 220, 230,**

240, 250, 260, 270, 280, 290, 300, and return path **310**. As described by Equation (29), block

210 calculates I_{kn}/J_k by integer division to yield an integer quotient Q_{kn} and an integer remainder

R_{kn} such that $R_{kn} < J_k$ for k=1, 2, ..., K. In block **220** as described by Equation (30), X_k is

10   computed by the summation Σ_k, from k=1 to k=K, of $Q_{kn}M_{kn}$. Also in block **220**, Equation (31)

updates the accumulators A_k for k=1, 2, ..., K. Decision block **230** and block **240** are executed in

sequence K times (i.e., blocks **230** and **240** for k=1, blocks **230** and **240** for k=2, ..., blocks **230**

and **240** for k=K). Block **250** is not executed until blocks **230** and **240** are executed in sequence

K times. Decision block **230** asks whether $A_k \geq J_k$. If YES then B is incremented by 1 and A_k is

15   decremented by J_k, as described by Equations (32) and (33), respectively, in block **240**. If NO,

block **240** is bypassed.

As shown in Equation (34), block **250** calculates X_n/Y by integer division to yield an

integer quotient Q_n and an integer remainder R_n such that $R_n < Y$. In block **260** as described by

Equation (35), Z_n is set equal to Q_n. Also in block **260**, Equation (36) updates the accumulator B.

20   Decision block **270** asks whether $B \geq Y$. If YES then Z_n is incremented by 1 and B is

decremented by Y, as described by Equations (37) and (38), respectively, in block **280**. If NO,

block **280** is bypassed. In block **290**, Equation (39) updates the calculation of Z in accordance with Equation (25) *supra*.

Decision block **300** asks whether there are more iterations to execute. If YES, the return path **310** directs the processing back to block **210** to begin the next loop iteration. If NO, the processing breaks the loop and executes post-processing in block **320**. The post-processing block may adjust the calculation of Z to reflect the fact that after completion of all iterations, the accumulators B and A_k (k=1, 2, ..., K) may have non-zero integer contents. Thus Z may be adjusted in the post processing block **320** according to:

$$Z = Z + [B + \Sigma_k (A_k/J_k)]/Y \tag{40}$$

wherein the summation over k in Equation (40) is from 1 to K. All calculations in Equation (40) should be performed in floating point. Thus, after Equation (40) is implemented, Z will be a floating point, or decimal, number.

The flow chart of FIG. 7 may be modified in any manner that is logically equivalent to FIG. 7 as shown herein, as would be understood by one of ordinary skill in the art. For example, if any $J_{k'} = 1$ then Equation (29) in block **210** could be simplified to $Q_{k'n} = I_{k'n}$ and $R_{k'n} = 0$. Additionally if $J_{k'} = 1$, then accumulator $A_{k'}$ need not be defined and Equation (26), Equation (31), and blocks **230** and **240** may be skipped for k=k', and the summation over k in Equation (40) does not include k=k'. As another example, if Y=1 (i.e., if $Z_n = X_n$ in Equation (23)), then Equation (34) in block **250** could be simplified to $Q_n = X_n$ and $R_n = 0$. Additionally if Y = 1, then accumulator B need not be defined and Equation (27), Equation (36), and blocks **270** and **280** may be skipped, and division by Y in Equation (40) may be skipped. As another example

END920010005US1   25

some or all of the intitializations block **200**, or mathematical equivalents thereof, could

alternatively be performed within the iteration loop of FIG. 7, but only at the beginning of the

first iteration, since the variables Z, B, and A_k (k=1, 2. ..., K) are iteration-dependent variables.

FIG. 8 illustrates use of the algorithm of FIG. 7 to compute Z for the following example:

$$Z_n = [(51/10)*3 + (42/4)]/6$$

and N=5 (i.e., 5 iterations). In this example, $X_n = (51/10)*3 + (42/4)$, Y=6, K=2, I_{1n}=51, J_1=10,

M_{1n}=3, I_{2n}=42, J_2=4, and M_{2n}=1. A floating point calculation yields X_n =25.8, Z_n =4.30, Z=21.50

(i.e., 5*4.30). Thus Z=21.50 is an exact value.

FIG. 8 shows that the method of FIG. 7, together with application of Equation (40) for the

post-processing of block **320** of FIG. 7, yields the exact value of Z=21.50. In applying Equation

(40) and using the values of A_1, A_2, and B from FIG. 8 at the end of iteration 5:

$$Z = Z + [B + (A_1/J_1) + (A_2/J_2)]/Y$$

$$= 21 + [2 + (5/10) + (2/4)]/6$$

$$= 21.50$$

which agrees with the exact value computed *supra*.

FIG. 9 illustrates a computer system **90**, in accordance with embodiments of the present

invention. The computer system **90** comprises a processor **91**, an input device **92** coupled to the

processor **91**, an output device **93** coupled to the processor **91**, and memory devices **94** and **95**

each coupled to the processor **91**. The input device **92** may be, *inter alia*, a keyboard, a mouse,

etc. The output device **93** may be, *inter alia*, a printer, a plotter, a computer screen, a magnetic

tape, a removable hard disk, a floppy disk, etc. The memory devices **94** and **95** may be, *inter*

alia, a hard disk, a dynamic random access memory (DRAM), a read-only memory (ROM), etc.

The memory device **95** includes a computer code **97**. The computer code or codes **97** includes at

least one of the algorithms associated with FIGS. 1-3, FIG. 2, FIG. 3, FIG. 6, and FIG. 7, as

described *supra* herein. The memory device **94** includes input data **96**. The input data **96**

5   includes input required by the computer code or codes **97**. The output device **93** displays output

from the computer code or codes **97**. For example, the output device **93** may include

BA_FINAL output from the algorithm of FIG. 1, BA_FINAL1 output from the algorithm of

FIG. 2, BA_FINAL2 output from the algorithm of FIG. 3, BA output from the algorithm of FIG.

6, and Z output from the algorithm of FIG. 7.

10   While FIG. 9 shows the computer system **90** as a particular configuration of hardware

and software, any configuration of hardware and software, as would be known to a person of

ordinary skill in the art, may be utilized for the purposes stated *supra* in conjunction with the

particular computer system **90** of FIG. 9. For example, the memory devices **94** and **95** may be

portions of a single memory device rather than separate memory devices.

15   While embodiments of the present invention have been described herein for purposes of

illustration, many modifications and changes will become apparent to those skilled in the art.

Accordingly, the appended claims are intended to encompass all such modifications and changes

as fall within the true spirit and scope of this invention.